

[Original] Claims

1. High-frequency measuring system for measuring a
5 device under test (19), comprising a measuring-
device unit (2) and at least one high-frequency
module (3, 24, 25),
characterised in that
each high-frequency module (3, 24, 25) can be
10 placed spatially separately from the measuring-
device unit (2), and each high-frequency module (3,
24, 25) can be connected to the measuring-device
unit (2) via a digital interface (23, 26, 27).
- 15 2. High-frequency measuring system according to claim
1,
characterised in that
the high-frequency module (3, 24, 25) comprises a
transmitter device and/or a receiver device (28,
20 29) for communication with a device under test
(19).
- 25 3. High-frequency measuring system according to claim
1 or 2,
characterised in that
the digital interface (23, 26, 27) is a serial
interface.
- 30 4. High-frequency measuring system according to claim
1 or 2,
characterised in that
the digital interface (23, 26, 27) is a parallel
interface.

5. High frequency measuring system according to any one of claims 1 to 4,
characterised in that
the digital interface (23, 26, 27) is an optical
5 interface.

6. High-frequency measuring system according to any one of claims 1 to 4,
characterised in that
10 the digital interface (23, 26, 27) is an electrical interface.

7. High-frequency measuring system according to any one of claims 1 to 6,
characterised in that
15 the at least one high-frequency module (3, 24, 25) is supplied with electrical energy via a power-supply unit (14, 40) independent from the measuring-device unit (2).
20

8. High-frequency measuring system according to any one of claims 1 to 7,
characterised in that
several identical ports (5.1, 5.2, 5.3) are
25 provided on the measuring-device unit (2) for the digital interface (23).

9. High-frequency measuring system according to any one of claims 1 to 8,
characterised in that
30 several different ports (5.1, 5.2, 5.3, 6.1, 6.2, 6.3) are provided on the measuring-device unit for the digital interface (23).

10. High-frequency measuring system according to any
one of claims 1 to 9,
characterised in that

5 a digitised intermediate-frequency signal can be
transmitted via the digital interface.

11. High-frequency measuring system according to any
one of claims 1 to 9,
characterised in that

10 control data and/or user data can be transmitted in
a standardised form via the digital interface and
that the at least one high-frequency module (24')
comprises means for processing a high-frequency
signal with regard to the transmission of data in
15 standardised form via the digital interface and/or
for processing the data transmitted in standardised
form with regard to at least one transmission
standard for the high-frequency signal.